

Vacuum glass lifter

Model

VA2+2T-RP



AIR Power supply
Compressed Air

The model VA2+2T-RP is a vacuum glass lifter specific for **indoor use**, as it is powered by compressed air. It is equipped with two centrally fixed suction pads and two suction pads placed on **removable and telescopic arms**.

The control unit is telescopic as well in order to offer proper management of the lifter also during load lifting.

The lifter features **pneumatic 0 - 90° rotation**. It is equipped with an audio-visual alarm unit that warns the operator of any possible dangerous situations. The vacuum gauge with coloured scale allows constant control of the vacuum level reached.



✓ Indoor use

✓ Telescopic frame

✓ Safety devices



Pneumatic rotation 90°

CE

made in
ITALY

Technical specification

Application	Glass panels
Lifting capacity	Max 400 kg
Suction pads	No. 2+2 round suction pads diameter 310 mm Lipped pads with safety ring
Pad spread	2 pads configuration - 650x310 mm 4 in-line pads configuration - 1321x310mm 4 in-line pads telescopic configuration - 2201x310 mm
Load movement	0 - 90° pneumatic rotation Vertically fixed
Operating system	Compressed air
Vacuum system	Single vacuum circuit with vacuum reserve and non return valve
Control	Manual on-off valve on the lifter's frame Release of the load by dual action security command Command box with telescopic handle
Standard features	Audible and visual low vacuum warning devices Vacuum gauge Vacuum filter Telescopic and removable pad arms

Technical drawings

